



**DSL30W1
DSM30W1**

Low Voltage Switches

Single gang design, momentary or latching operation. Compatible with all Hubbell low voltage sensors and Load:Logic® Centralized and Distributed Control Systems. 100mA @ 30V DC max.

Description	Color	Catalog Number
Low voltage switch, latching, 1 button.	Ivory	DSL3011
	Light Almond	DSL30LA1
	White	DSL30W1
Low voltage switch, momentary, 1 button.	Ivory	DSM3011
	Light Almond	DSM30LA1
	White	DSM30W1
Low voltage switch, momentary, 2 buttons.	Ivory	DSM3012
	Light Almond	DSM30LA2
	White	DSM30W2

Note: Wallplate sold separately.



CU300ELC

Emergency Lighting Controls

20 Amps, 120/277V AC, NC isolated contacts UL924 listed for emergency circuits. 0-10V dimming override.

Description	Catalog Number
Emergency lighting control unit.	CU300ELC
Remote test switch with engraved wallplate.	RTPB10W

Note: See page E-26 for technical specifications.



**CU300A(M),
CU347A**

Control Units

The CU300 series provides 24V DC power supply for sensors or sensor/Add-A-Relay combinations. The control units contain an internal relay for the control of an external load. Control units are plenum rated cULus Listed.

Description	Catalog Number
Auto ON operation, 100-277V AC, 50/60Hz for use with 1 to 4 ATD, ATU, ATP and AD2240 series sensors.	CU300A
Manual ON operation, 100-277V AC, 50/60Hz for use with 1 to 4 ATD, ATU, ATP and AD2240 series sensors.	CU300M
Auto or manual ON operation, 100-277V AC, 50/60Hz for use with 1 to 6 ATD, ATU, ATP, AHP and AD2240 series sensors, heavy duty latching relay for reactive loads and automatic receptacle control.	CU300HD

*Note: See page E-26 for technical specifications.
For Assembled in USA units Add suffix "U".*



CU300HD



AAR

Add-A-Relay

Hubbell AAR Add-A-Relay contains an internal relay for control of an external load. The AAR requires a 24V DC power supply from the Hubbell CU series control unit. AAR units are typically used when multiple zone control is desired or the load exceed the maximum load rating of a single control unit.

Description	Catalog Number
Auto ON operation, 120-277V AC, 50/60Hz. Requires a CU300 series control unit; suitable for lighting loads.	AAR
Auto or manual ON operation, 100-277V AC 50/60Hz. Requires a CU300 series, heavy duty latching relay; suitable for automatic receptacle control applications.	AAR20P

Note: See page E-26 for technical specifications.



AAR20P



AAR10C277

Enclosed 10 Amp SPDT Relays

Description	Catalog Number
Enclosed relay 10 Amp SPDT with 10-30V AC/DC/120V AC coil.	AAR10C120
Enclosed relay 10 Amp SPDT with 10-30V AC/DC/208-277V AC coil.	AAR10C277