

Traditional Flush Furniture Feed FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

Large Capacity, Single-Service Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Color/Material	Catalog Number
Large Capacity, Single-Service Through Floor Fitting with (1) 2 in. EMT stem. Will accommodate up to 36 Category 6 cables.	PT2FIT	Large Capacity Cover/Flange	Brass Finish Black Gray	FF2BRS FF2BK FF2GY
Specifications: 1- to 2-hour fire rating - Single-Service, Power or Data - For 2¼ to 7 in. floor thickness - UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area - Approved for use in the City of Chicago		Specifications: - Cover/flange with 1¼ in. and 2 in. trade size combination knockout - Painted aluminum cover and flange - Approved for use in the City of Chicago		

Note: See page Q-42 for technical information.

Flush Furniture Feed FRPT, One-Piece Units

Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Poke-Through	Black Gray Ivory	PT73FFSDBK PT73FFSDGY PT73FFSDI	Single-Service Furniture Feed Poke-Through	Black Gray Ivory	PT7FFSDGY PT7FFSDI
Complete assembled unit includes: - PT73SD floor fitting - Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power - Painted aluminum flange			Complete assembled unit includes: - PT71SD floor fitting - Aluminum cover with (1) KO to accept a ¾ in. connector - Painted aluminum flange		

Note: See page Q-42 for technical information.

Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Catalog Number
3-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power and (2) ½ in. low voltage conduit holes.	PT73SD	Single-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power or low voltage applications.	PT71SD
Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)		Specifications: - For 2¼ to 7 in. floor thickness - UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area	

Service Fittings

Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Service Fitting	Black Gray Ivory	FRF3BK FRF3GY FRF3I	Single-Service Furniture Feed Service Fitting	Brass Finish Black Gray	FRF1BRS FRF1BK FRF1GY
Complete assembled unit includes: - Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power - Painted aluminum flange			Complete assembled unit includes: - Aluminum cover with (1) KO to accept a ¾ in. connector - Painted aluminum flange		

Note: See page Q-33 for 3 Inch FRPT accessories.
See page Q-42 for technical information.