

**30 Amp, 3Ø 480 and 3Ø 600 Volts AC**  
**3 Pole, 4 Wire, Grounding**



**HBL2731SW**




**HBL2731S**



**HBL2731**



**HBL2735SW**



**HBL2735**

Dimensions in Inches (mm)

## Plugs

### Watertight Safety-Shroud®

| Description                                | Cord Dia.           | Catalog Number                    |
|--------------------------------------------|---------------------|-----------------------------------|
| Black Valox® housing, white Valox® clamps. | .350"-1.150" (9-29) | <b>HBL2731SW</b> <b>HBL2741SW</b> |

### Safety-Shroud®

| Description                                                                                       | Cord Dia.           | Catalog Number                  |
|---------------------------------------------------------------------------------------------------|---------------------|---------------------------------|
| Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies. | .350"-1.150" (9-29) | <b>HBL2731S</b> <b>HBL2741S</b> |

Note: See page B-42 for accessories.

### Insulgrip®

| Description                        | Cord Dia.           | Catalog Number                    |
|------------------------------------|---------------------|-----------------------------------|
| Black and white nylon.             | .350"-1.150" (9-29) | <b>HBL2731</b> <b>HBL2741</b>     |
| Corrosion resistant, yellow nylon. | .350"-1.150" (9-29) | <b>HBL27CM31</b> <b>HBL27CM41</b> |

Note: See page B-54 for accessories.

## Flanged Inlets

### Watertight Safety-Shroud®

| Description                     | Catalog Number                    |
|---------------------------------|-----------------------------------|
| Gray Valox® housing and flange. | <b>HBL2735SW</b> <b>HBL2745SW</b> |

Note: See page B-56 for accessories.

### Insulgrip®

| Description               | Catalog Number                |
|---------------------------|-------------------------------|
| Nylon casing, back wired. | <b>HBL2735</b> <b>HBL2745</b> |

Note: See page B-54 for accessories.

See pages B-71 and B-72 for technical information on Twist-Lock and Watertight Safety-Shroud devices.



30A 3Ø 480V AC  
NEMA L16-30P  
10 HP



30A 3Ø 600V AC  
NEMA L17-30P

**HBLMITL** - For use with Watertight Safety-Shroud receptacles, see page B-43.



Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.